



DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD

Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone ,  
Humen town ,Guangdong province ,China Zip Code: 523925

TEL:86-769 -88920358 ( 8 line ) FAX:86-769 -87093015

<http://www.jing-one.com.cn> [E-mail:chitiezhang@hotmail.com](mailto:chitiezhang@hotmail.com)

## Cable Cutting machine

Linkage type wire cutting machine



Dongguan Jing One Wire & Cable Machine Co.,Ltd



Dongguan Jing One Wire & Cable Machine Co.,Ltd

Standard type cutting machine as below picture



### Standard type cutting machine

This kind of machine should be used together with pay-off machine and tension frame, cutting ability scope: round wire  $\phi 4.0\text{mm}$ - $\phi 10\text{mm}$ , flat wire thickness: 2.0mm-4mm, width 4.5mm-11mm, it main motor using the imported motor, the speed of wire cutting reach up to 200m/min, max 150 strips per minute. The length of conveyor can be setting according to the customer requirement. The biggest features for in the process of operation, can continuous wire cutting. Suitable for working environment of high-speed and saving the manpower, high efficiency and saves time and effort, will suit your work needs.

### Linkage type wire cutting machine

This kind of machine should be used together with pay-off machine and tension frame, cutting ability scope: round wire  $\phi 4.0\text{mm}$ - $\phi 10\text{mm}$ , flat wire thickness: 2.0mm-4mm, width 4.5mm-11mm, it main motor using the imported motor, the speed of wire cutting reach up to 180m/min, max 150 strips per minute. The length of conveyor can be setting according to the customer requirement. The biggest features for in the process of operation, can continuous wire cutting. Suitable for working environment of high- speed and saving the manpower, high efficiency and saves time and effort, will suit your work needs.

Model	Standard type cutting machine	Linkage type wire cutting machine
Cutting speed	200m/min, max 150 strips/min	180m/min, max 150 strips/min
Cutting capacity	Round cable $\phi 4.0\text{m/m}$ - $\phi 10\text{m/m}$ Parallel cable 2.0m/m-4.0m/m Width 5.0m/m-10m/m	Round cable $\phi 4.0\text{m/m}$ - $\phi 10\text{m/m}$ Parallel cable 2.0m/m-4.0m/m Width 4.5m/m-11m/m
Min. Removal length	600m/m	600m/m
Cutting precision	$\pm 3\text{mm}$	$\pm 3\text{mm}$
Get-line	Fight line	Fight line
Cable feeding Way	iron axes, wood axes	Working with PVC extruder

<b>Cable feeding axes diameter</b>	(a)700m/m-950m/m (b)900m/m-1050m/m (c)1000m/m-1200m/m	
<b>Engaged horse</b>	VS motor 2HP(main case) motor 1HP(feeding machine)	Motor 2HP (main case) Motor 1HP (feeding machine)
<b>Engaged power</b>	380V + wire, 50HZ	380V + wire, 50HZ
<b>Repudiated area</b>	(L)9m×(W)2m×(H)1.8m(Standard length)	(L)5.5m×(W)2m×(H)1.8m(Standard length)
<b>Weight</b>	Tension rack250kg conveyer (four meter)320kg main unit520kg wire unreeling machine 585kg gross weight 1630kg	Tension rack 520kg conveyer( four meter)(4m) 320kg Total weight840kg