



DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD
 Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone ,
 Humen town ,Guangdong province ,China Zip Code: 523925
 TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015

<http://www.jing-one.com.cn> [E-mail:chitiezhang@hotmail.com](mailto:chitiezhang@hotmail.com)

Teflon Cable Extruder



Application: Suitable for FEP (fluorinated Ethylene Propylene, also known as F46), FPA and ETFE (also known as F40) etc. fluorine plastic production.

Screw barrel: Adopt new No.3 steel GH113 (With the United States GDA material) corrosion resistant and High temperature resistant.

Crosshead: Adopt new No.3 king steel GH113 material special fixed centering crosshead or manual centering crosshead.

Heating system: Adopt high temperature resistant copper alloys heater.

Quality control: Equipped with diameter inspection feedback device, full process control of product outer diameter and concentricity diameter.

Electronic control: Imported converter + PLC touch screen control.

Model	JO-30mm	JO-45mm	JO-65mm
Screw diameter	φ30mm	φ45mm	φ65mm
Screw L/D ratio	25:1 Special type screw	25:1 Special type screw	25:1 Special type screw
Temperature control	6Segment	6Segment	7Segment
Main motor power	10HP	15HP	30HP
Extrusion output	20kg/h	45kg/h	100kg/h
Conductor diameter	0.1-1.8mm	0.4-6.0mm	0.6-8.0mm

Insulation back outer diameter	0.2-2.0mm	0.6-8.0mm	1.0-10.0mm
Electric control	PLC or Common		