



DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD
 Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone ,
 Humen town ,Guangdong province ,China Zip Code: 523925
 TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015

<http://www.jing-one.com.cn> [E-mail:chitiezhang@hotmail.com](mailto:chitiezhang@hotmail.com)

1000mm Cantilever type single twister



Application : Mainly used for twisting/cabling CAT5E/6E , communication cable , control cable etc high frequency cable and center belting or side belting.

Model	JO-φ1000mm
Application	PVC/PE covered core wire or copper twisting and center belting or side belting
Feed wire shaft size	φ400mm-φ500mm-φ630mm
Winding shaft size	Standard punch iron bobbin: Outer diameterφ1000mm×Outer width750mm×inner width630mm×inner holeφ80mm
Application wire diameter	φ0.6mm-5.0mm
Max twisting outer diameter	φ25mm
Lay length	30-300mm Step-less adjustable
Rotate speed	500rpm
Upper and lower wire bobbin	Hydraulic lifting
Method of traverse	Double screw rod reciprocating traverse
Take-up tension	Pneumatic
Brake	Pneumatic brake
Twist direction	Left and right can freely selected

Taking device	Center lapping or side packing
	Left and right can freely selected
	Suitable for the cotton paper, wheat belt, aluminum tape
	Bobbin diameter:φ350mm,hole diameter:φ50mm,Width:8~30mm