



DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD
 Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone ,
 Humen town ,Guangdong province ,China Zip Code: 523925
 TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015
<http://www.jing-one.com.cn> [E-mail:chitiezhang@hotmail.com](mailto:chitiezhang@hotmail.com)

630mm-1000mm Frame type single twister



Dongguan Jing One Wire & Cable Machine Co.,Ltd

Application:

Suitable for various the power wire, date wire & cable, communication wire & cable and other special wire & cable core wire cabling twist, meanwhile completed center wrapping and side lay wrapping.

Model	JO-φ630mm	JO-φ800mm	JO-φ1000mm
Application	PVC/PE covered core wire or copper twisting and center belting or side belting		
Feed wire shaft size	φ400mm-φ500mm	φ400mm-φ500mm	φ400mm-φ500mm-φ630mm
Winding shaft size	Outer diameterφ630x Outer width 475x inner width 400x inner hole φ56mm	Outer diameterφ800x Outer width 600x inner width 500x inner hole φ80mm	Outer diameterφ1000x Outer width 750x inner width 630x inner hole φ80mm

Application wire diameter	φ0.6mm-3.0mm(Soft structure)	φ1.0mm-5.0mm(Soft structure)	φ1.2mm-5.0mm(Soft structure)
Outer diameter	φ15mm	φ20mm	φ25mm
Lay length	20-200mm Step-less adjustable	30-300mm Step-less adjustable	30-300mm Step-less adjustable
Rotate speed	700rpm	500rpm	500rpm
Upper and lower wire bobbin	Pneumatic lifting	Hydraulic lifting	
Method of traverse	Double screw rod reciprocating traverse		
Take-up tension	Pneumatic		
Brake	Pneumatic brake		
Twist direction	Left and right can freely selected		
Wrapping device	enter lapping or side packing		
	S、Z Left and right can freely selected		
	Suitable for the cotton paper, Mylar, aluminum tape		
	Disk Drive:φ350mm Hole diameter:φ50mm Width:8-30mm	Disk Drive:φ350mm Hole diameter:φ50mm Width:8-30mm	Disk Drive:φ350mm Hole diameter:φ50mm Width:8-30mm