DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone , Humen town ,Guangdong province ,China Zip Code: 523925 TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015 http://www.jing-one.com.cn <u>E-mail:chitiezhong@hotmail.com</u>

Horizontal type double-layer taping machine



The machine is horizontal double-layer wrapping machine(paper tape, aluminum foil)with rotation plate wrapping on the core wire, own single wrapping head. Mainly uses for the electric wire, the strength cable, controls cable and optical cable etc. insulated wire core mica tape wrapping, the fireproof electric wire electric cable mainly is suitable for power plant, airport, ships, high rise construction, subway, underground street and recreation area.

Working principle:

The machine is single head wrapping, A. C. motor passed belt to drive, drive the gear transmission of through the cone gear, make the wrap bobbin left and right direction

to rotation, the core wire passed capstan wheel with single wrap positive and negative rotation, wrap the tape into core wire, realize once wrapping, by adjustment step-less speed changer can be changed speed of capstan wheel to conform different lay of wrap needs. We can produce single head, double head and three head wrapping machine according to customer's need.

Mode	JO-40	JO-40L	JO-50	JO-50L
Mode	30-40	JO-40L	30-30	JO-30L
Taking bobbin specification	400mm	400mm	500mm	500mm
Cable outer diameter	25mm	55mm	25mm	55mm
Tape bobbin	2500rpm	2500rpm	2500rpm	2500rpm
Reserve capacity of tape bobbin	600mm	600mm	800mm	800mm
Cable take-up wire spool	630mm-800mm, 800mm-1250mm, 1250mm-1600mm			
Double wheels	300mm	500mm	300mm	500mm
Caterpillar	300kg	500kg	300kg	500kg
Taping machine power	2.2kw	2.2kw	3.7kw	3.7kw
Tape tension	1.2kg	1.2kg	1.2kg	1.2kg