

## **DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD**

Address: No.13, nanxing Road, Beizha nanfang industrial zone, Humen town, Guangdong province, China Zip Code: 523925

TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015

http://www.jing-one.com.cn E-mail:chitiezhong@hotmail.com

## Portal type motorized pay off stand





The machine is composed of gantry pay-off machine, electric control box and rock arm type extension frame. The pay-off extension can be adjusted according to needs and feedback signal issued by rock arm type extension frame is used to realize the constant extension during the pay-off process, thus, the deformation of copper wire or core wire during the pay-off process is avoided. The line wheel installs or lifts off hydraulic lifting and manual clamp position. The machine is the necessary equipment for manufacturing communication, controlling computer network and other cables with relatively high requirements.

Model	JO-400mm	JO-500mm	JO-630mm	JO-800mm
Feed wire diameter	φ0.32-φ4mm	φ0.32-φ4mm	φ0.32-φ4mm	φ0.32-φ4mm
Pay-off speed	60-80m/min	60-80m/min	60-80m/min	60-80m/min
Pay-off bobbin specification	φ300-φ400mm	φ400-φ500mm	φ500-φ630mm	φ630-φ800mm
Mainframe power	2.2KW	3.7KW	5.5KW	7.5KW
Machine weight	866kg	966kg	1066kg	1166kg
Upper and lower wire bobbin	Motor automatic lifting			

Model	JO-400mm	JO-500mm	JO-630mm	JO-800mm
Feed wire diameter	φ0.75-φ4.5mm	φ0.75-φ1.5mm	φ0.75-φ3.0mm	φ0.75-φ5.0mm
Mainframe power	0.75kw	0.75kw	1.5kw	2.2kw

Upper and lower	No-axis type
Control wire	The device under wire stored holder could send a signal to transducer for controlling
speed	the motor speed
Tension	Automatic tensile force has been selected in factory

Model	JO-800mm	JO-1000mm
Feed wire diameter	φ0.32-φ4mm	φ0.32-φ4mm
Pay-off speed	60-800m/min	60-800m/min
Pay-off bobbin specification	φ800mm	φ1000mm
Mainframe power	3.7KW	3.7KW
Machine weight	800kg	860kg
Upper and lower wire		-
bobbin	Motor automatic lifting	
Device wire bobbin	Pneumatic device	