



DONGGUAN JING ONE WIRE & CABLE MACHINE CO.LTD
Address : No.13 ,nanxing Road ,Beizha nanfang industrial zone ,
Humen town ,Guangdong province ,China Zip Code: 523925
TEL:86-769 -88920358 (8 line) FAX:86-769 -87093015

<http://www.jing-one.com.cn> [E-mail:chitiezhang@hotmail.com](mailto:chitiezhang@hotmail.com)

Various Extruder Line



I .Application: Suitable for PVC, LDPE, XLPE, LSHF, TPU etc. Insulation material of the wire and cable monochrome, double-color, double-layer, tri-layer extrusion working.

II. Equipment model and specification classify:

1. According to the particularity of cable technical requirements, optional various peripheral equipments by the company design and production , can be make up the following various production lines:

Production line of the UL electronic wire and special cable

Production line of the power wire . Building wire and insulation sheath

Production line of the telephone cable and military products

Production line of the power wire , audio wire , network cable and insulation sheath

Production line of the electrical cable and insulation sheath

Extruder production line of the wire . Cable insulation sheath

50+Φ35 Extruder Production line

Production line of the LDPE , HDPE(Low density, high density)foaming

Production line of the low smoke halogen free and small smoke low halogen

45-Φ90 Physical foaming extruder

Extruder production line of the (PLC) full computer control and fluorine plastic Teflon(high temperature)

Silicone cable extruder machine

Extrusion production line of the colored lights

Extruder production line of the blank pipe. Wire-rope locking rope and insulation sheath

Flexible PVC/PE hose production line

Extrusion production line of the car cable

Series extrusion production line of the LAN wire

2. According to the different extrusion—screw diameter can be divided into Φ30, Φ35, Φ40, Φ45, Φ50, Φ55, Φ60, Φ65, Φ70, Φ80, Φ90, Φ100, Φ120 etc.
3. According to the different control methods can be divided into the PLC control type and traditional control type.